

CJV200 Series



Eco-Solvent roll-based print & cut device

32"

54"

64"

Total sign printing package

High value in a small footprint, the CJV200 provides indoor and outdoor durable printing with an integrated cutter and easy-to-use software for the perfect stand-alone bundle.

- Easily produce indoor and outdoor prints on a large selection of media with 'one printer to do it all' versatility in a small footprint.
- Enjoy outstanding quality and productivity, plus the industry's best outdoor durability at an attractive price point.
- Print a wide range of applications using this complete system with print & cut device, software, and a range of inks.
- Easy to use with paired RIP software for extreme accuracy when creating instant decals and large wall graphics.
- Outstanding quality and productivity at an attractive price point.
- Mimaki Core Technologies deliver exceptional results, economically, and with maximum productivity.
- Select from three model widths to suit your production needs.
- Three year Parts warranty - including Print Heads.

Mimaki® CJV200 Series

Printhead	On-demand piezo print head (single)		
Print resolution	X: 600,1200 dpi Y: 600,900,1200 dpi		
Print speed (4 color mode)	183 sqft/hr (17 sqm/hr)		
	CJV200-75	CJV200-130	CJV200-160
Maximum print width	31.5 in (800 mm)	53.6 in (1361 mm)	63.4 in (1610 mm)
Maximum media width	31.9 in (810 mm)	53.9 in (1371 mm)	63.8 in (1620 mm)
Weight (uncrated)	231.4 lbs. (105 kg)	286.6 lbs. (130 kg)	308.6 lbs. (140 kg)
Ink Type/Color	Eco-Solvent inks		
	SS22 (C, M, Y, K, Lc, Lm, Lk, Or)		
Ink Package Size	440ml Cartridges		
	1L Bulk Ink Package (for use with optional Mimaki Bulk Ink System)		
Media Thickness	up to 0.04 in (1 mm)		
Rolled Media Weight	55 lbs. (25 kg)		
Certifications	VCCI class A, FCC class A, ETL IEC 62368-1, CE Marking (EMC, Low voltage, Machinery directive, and RoHS), CB, REACH, Energy Star, RCM, EAC, KC, UKCA		
Interface	USB 2.0 Hi-speed Ethernet 1000 BASE-T		
Power Supply	AC (100-120V / 200-240V±10%) × two 50/60Hz±1Hz		
Power Consumption	Max. 1320W x2 Sleep mode: 4.5W		
Operational Environment	Temperature: 68–86 °F (20–30 °C)		
	Humidity: 35–65%		
Dimensions (W x D x H)	CJV200-75: 77 in W x 29.5 in D x 54 in H (1960 mm W x 748 mm D x 1370 mm H)		
	CJV200-130: 99 in W x 29.5 in D x 54 in H (2520 mm W x 748 mm D x 1370 mm H)		
	CJV200-160: 109 in W x 29.5 in D x 54 in H (2770 mm W x 748 mm D x 1370 mm H)		
Options	Mimaki Bulk Ink System, NCU OPT, MBIS BKT OPT, 45kg Media Support		

Eco-Solvent roll-based print & cut device

32"

54"

64"

*La fábrica se reserva el derecho de modificar las especificaciones sin previo aviso | Ver.: 13-05-2025